

Technical specifications



	EUROPEAN CLASSIFICATION	TOTAL THICKNESS	WEAR LAYER	WEAR LAYER TREATMENT	TOTAL WEIGHT	WIDTH	STANDARD LENGTH	WEIGHT OF STANDARD ROLL	SLIP RESTRAINT	INFLAMMABILITY	ACOUSTICAL INSULATION	THERMAL RESISTANCE	RESIDENTIAL WARRANTY	COMMERCIAL WARRANTY
Super														
Heritage	23 - 32	ca. 2,20 mm	ca. 0,40 mm	PU / Natural Feel	ca. 2063 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 128 - 192 - 256 kg	R10	Bfl-S1	15 dB	0,0088 m ² K/W	15 years	5 years
Ultimate Wood	23 - 32	ca. 2,60 mm	ca. 0,35 mm	PU / Natural Feel	ca. 1800 g/m ²	2 - 3 - 4 m	ca. 25 m	ca. 94 - 141 - 188 kg	R11	Cfl-S1	18 dB	0,0104 m ² K/W	15 years	
Ultimate Stone	23 - 32	ca. 2,60 mm	ca. 0,35 mm	PU / Natural Feel	ca. 1800 g/m ²	2 - 3 - 4 m	ca. 25 m	ca. 94 - 141 - 188 kg	R11	Cfl-S1	18 dB	0,0104 m ² K/W	15 years	
Solid														
Luxury Classics	23	ca. 3,70 mm	ca. 0,30 mm	Natural Feel	ca. 2250 g/m ²	2 - 3 - 4 m	ca. 25 m	ca. 117 - 175 - 233 kg	R10*	Cfl-S1	20 dB	0,0148 m ² K/W	10 years	
Luxury Trends	23 - 31	ca. 3,70 mm	ca. 0,30 mm	Natural Feel	ca. 2250 g/m ²	2 - (3) - 4 m**	ca. 25 m	ca. 117 - (175) - 233 kg	R10	Cfl-S1	20 dB	0,0148 m ² K/W	10 years	
Victoria	23 - 31	ca. 3,70 mm	ca. 0,30 mm	Natural Feel	ca. 2250 g/m ²	2 - (3) - 4 m**	ca. 25 m	ca. 117 - (175) - 233 kg	R10	Cfl-S1	20 dB	0,0148 m ² K/W	10 years	
Smart														
Atlas	22	ca. 3,80 mm	ca. 0,20 mm	Natural Feel	ca. 2250 g/m ²	2 - (3) - 4 m**	ca. 22 m	ca. 103 - (155) - 206 kg	R10	Cfl-S1	21 dB	0,0152 m ² K/W	7 years	
Bingo	22	ca. 2,80 mm	ca. 0,20 mm	Natural Feel	ca. 1600 g/m ²	2 - (3) - 4 m**	ca. 30 m	ca. 100 - (150) - 200 kg	/	Cfl-S1	18 dB	0,0112 m ² K/W	5 years	
Blush	22	ca. 2,00 mm	ca. 0,20 mm	PU / Natural Feel	ca. 1500 g/m ²	2 - (3) - 4 m**	ca. 30 m	ca. 94 - (141) - 188 kg	R11	Cfl-S1	16 dB	0,0080 m ² K/W	5 years	
Bubblegum & Liquorice	22	ca. 2,80 mm	ca. 0,20 mm	Natural Feel	ca. 1700 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 106 - 159 - 212 kg	R10*	Cfl-S1	18 dB	0,0112 m ² K/W	7 years	
Colori	22	ca. 2,80 mm	ca. 0,20 mm	Natural Feel	ca. 1600 g/m ²	2 - (3) - 4 m**	ca. 30 m	ca. 100 - (150) - 200 kg	/	Cfl-S1	18 dB	0,0112 m ² K/W	5 years	
Country Woods	23	ca. 2,50 mm	ca. 0,25 mm	Natural Feel	ca. 1550 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 97 - 146 - 194 kg	R11	Cfl-S1	16 dB	0,0100 m ² K/W	7 years	
Eco	21	ca. 1,15 mm	ca. 0,15 mm	Natural Feel	ca. 1100 g/m ²	2 - (3) - 4 m**	ca. 35 m	ca. 81 - (122) - 162 kg	/	Bfl-S1	12 dB	0,0046 m ² K/W	5 years	
Fusion	22	ca. 2,80 mm	ca. 0,20 mm	Natural Feel	ca. 1600 g/m ²	2 - (3) - 4 m**	ca. 30 m	ca. 100 - (150) - 200 kg	R10	Cfl-S1	18 dB	0,0112 m ² K/W	5 years	
Grip Supreme	22	ca. 2,80 mm	ca. 0,20 mm	Natural Feel	ca. 1600 g/m ²	2 - (3) - 4 m**	ca. 30 m	ca. 100 - (150) - 200 kg	R10	Cfl-S1	18 dB	0,0112 m ² K/W	5 years	
Luna	22	ca. 2,00 mm	ca. 0,20 mm	Natural Feel	ca. 1450 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 91 - 137 - 182 kg	R10	Cfl-S1	16 dB	0,0080 m ² K/W	5 years	
Materia	23	ca. 2,50 mm	ca. 0,25 mm	Natural Feel	ca. 1550 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 97 - 146 - 194 kg	R10-R11*	Cfl-S1	16 dB	0,0100 m ² K/W	7 years	
Mosa	22	ca. 3,50 mm	ca. 0,20 mm	Natural Feel	ca. 1960 g/m ²	2 - (3) - 4 m**	ca. 25 m	ca. 102 - (153) - 204 kg	R10	Cfl-S1	20 dB	0,0140 m ² K/W	5 years	
Nova	23	ca. 2,50 mm	ca. 0,25 mm	Natural Feel	ca. 1550 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 97 - 146 - 194 kg	R10	Cfl-S1	16 dB	0,0100 m ² K/W	7 years	
Presto	22	ca. 2,80 mm	ca. 0,20 mm	Natural Feel	ca. 1600 g/m ²	2 - (3) - 4 m**	ca. 30 m	ca. 100 - (150) - 200 kg	R10	Cfl-S1	18 dB	0,0112 m ² K/W	5 years	
Trend	22	ca. 2,80 mm	ca. 0,20 mm	Natural Feel	ca. 1600 g/m ²	2 - (3) - 4 m**	ca. 30 m	ca. 100 - (150) - 200 kg	R10	Cfl-S1	18 dB	0,0112 m ² K/W	5 years	
Semi-Contract														
Colca	23 - 32 - 41	ca. 2,00 mm	ca. 0,40 mm	Natural Feel	ca. 1850 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 115 - 173 - 230 kg	R10	Bfl-S1	15 dB	0,0080 m ² K/W	15 years	5 years
Elite	23 - 32	ca. 2,00 mm	ca. 0,40 mm	Natural Feel	ca. 1850 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 115 - 173 - 230 kg	R9	Bfl-S1	15 dB	0,0080 m ² K/W	15 years	5 years
Elites	23 - 32	ca. 2,20 mm	ca. 0,40 mm	PU / Natural Feel	ca. 2050 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 127 - 191 - 254 kg	R10	Bfl-S1	15 dB	0,0088 m ² K/W	15 years	5 years
Gala	23 - 32	ca. 2,00 mm	ca. 0,40 mm	PU / Natural Feel	ca. 1850 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 115 - 173 - 230 kg	R10	Bfl-S1	15 dB	0,0080 m ² K/W	15 years	5 years
Prisma	23 - 32	ca. 2,20 mm	ca. 0,40 mm	PU / Natural Feel	ca. 2050 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 127 - 191 - 254 kg	R10	Bfl-S1	15 dB	0,0088 m ² K/W	15 years	5 years
Vision	23 - 32	ca. 2,20 mm	ca. 0,40 mm	Natural Feel	ca. 1850 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 115 - 173 - 230 kg	R10	Bfl-S1	15 dB	0,0080 m ² K/W	15 years	5 years
Textile														
Chrometex	23 - 31	ca. 3,80 mm	ca. 0,50 mm	PU / Natural Feel	ca. 2500 g/m ²	2 - 3 - 4 m	ca. 22 m	ca. 114 - 171 - 228 kg	R11	Cfl-S1	17 dB	0,0160 m ² K/W	15 years	
Gatsby	23 - 32	ca. 2,80 mm	ca. 0,40 mm	PU / Natural Feel	ca. 1950 g/m ²	2 - (3) - 4 m**	ca. 30 m	ca. 121 - (182) - 242 kg	R10 - R11*	Cfl-S1	17 dB	0,0112 m ² K/W	15 years	
Greentex	23 - 31	ca. 3,10 mm	ca. 0,40 mm	PU / Natural Feel	ca. 2100 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 130 - 195 - 260 kg	R10 - R11*	Cfl-S1	18 dB	0,0124 m ² K/W	15 years	
Supertex	23 - 31	ca. 3,80 mm	ca. 0,40 mm	Natural Feel	ca. 2400 g/m ²	2 - 3 - 4 m	ca. 22 m	ca. 106 - 158 - 211 kg	R10	Cfl-S1	18 dB	0,0152 m ² K/W	15 years	
Texmark	23 - 32	ca. 2,80 mm	ca. 0,40 mm	PU / Natural Feel	ca. 1950 g/m ²	2 - (3) - 4 m**	ca. 30 m	ca. 121 - 182 - 242 kg	R10 - R11*	Cfl-S1	17 dB	0,0112 m ² K/W	15 years	
Verdi	23 - 31	ca. 4,00 mm	ca. 0,40 mm	Natural Feel	ca. 2400 g/m ²	2 - 3 - 4 m	ca. 23 m	ca. 115 - 172 - 229 kg	R10*	Cfl-S1	17 dB	0,0160 m ² K/W	15 years	
Comfytex	23	ca. 2,60 mm	ca. 0,25 mm	PU / Natural Feel	ca. 1650 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 103 - 155 - 206 kg	R10 - R11*	Cfl-S1	16 dB	0,0104 m ² K/W	10 years	
Trendtex	23	ca. 2,35 mm	ca. 0,25 mm	PU / Natural Feel	ca. 1700 g/m ²	2 - 3 - 4 m	ca. 30 m	ca. 106 - 159 - 212 kg	R11	Cfl-S1	Awaiting test	0,0104 m ² K/W	10 years	
Grip Supreme TB	22	ca. 2,50 mm	ca. 0,20 mm	Natural Feel	ca. 1650 g/m ²	2 - (3) - 4 m**	ca. 30 m	ca. 103 - (155) - 206 kg	R10*	Cfl-S1	16 dB	0,0100 m ² K/W	5 years	
Texas New	22	ca. 2,50 mm	ca. 0,20 mm	Natural Feel	ca. 1650 g/m ²	2 - (3) - 4 m**	ca. 30 m	ca. 103 - (155) - 206 kg	R10*	Cfl-S1	16 dB	0,0100 m ² K/W	5 years	